Dane aktualne na dzień: 05-11-2026 10:42

Link do produktu: https://www.akumulatory24.pl/yuasa-np1-2-12-p-2860.html



YUASA NP1,2-12 AGM 1,2Ah 12V NP 1,2-12

Cena brutto	**79,99 zł**
Cena netto	**65,03 zł**
Dostępność	**Dostępny**
Czas wysyłki	**24 godziny**
Kod EAN	**4016138323634**
Producent	**Yuasa**
Napięcie [V]	**12**
Pojemność [Ah]	**1,2**
Polaryzacja [+-]	**Prawy Plus**
Długość [L mm]	**97**
Szerokość [W mm]	**48**
Wysokość [H mm]	**54**

Opis produktu

Zastosowanie:

- Systemy UPS
- Systemy nadzoru
- Systemy alarmowe
- Kasy fiskalne
- Zasilanie urządzeń telewizji kablowej
- Sprzęt medyczny
- Zabawki elektryczne
- Motocykle i skutery
- Automatyka przemysłowa

Korzyści z użytkowania akumulatora:

- Maksymalne komfort i bezpieczeństwo
- Ognioodporność (Pojemnik, pokrywa i osłona zaworu zbudowane są z trudnopalnej żywicy ABS)
- Hermetyczna konstrukcja (Konstrukcja akumulatorów YUASA zapewnia całkowitą ochronę przed wyciekiem elektrolitu
- Wysokowydajne płyty (Płyty ze stopu ołowiowo-wapniowego zapewniają długą żywotność oraz doskonałą charakterystykę eksploatacji)
- Mały stopień samorozładowania (Dzięki zastosowaniu kratki ze stopu ołowiowo-wapniowego stopień samorozładowania akumulatorów NP wynosi 3% pojemności znamionowej w skali miesiąca w zakresie temperatur 20 °C)
- całkowicie bezobsługowy (wg normy EN)


Yuasa Technical Data Sheet

Yuasa NP1.2-12 Industrial VRLA Battery



Specifications	
Nominal voltage (V)	12
20-hr rate Capacity to 10.5V at 20°C (Ah)	1.2
10-hr rate Capacity to 10.8V at 20°C (Ah)	1.1
Dimensions	
Length (mm)	97 (±1)
Width (mm)	48 (±1)
Height over terminals (mm)	54.5 (±2)
Mass (kg)	0.58
Terminal Type	
FASTON - Quickfit / release (JST where stated)	4.75
Operating Temperature Range	
Storage (in fully charged condition)	-20°C to +60°C
Charge	-15°C to +50°C
Discharge	-20°C to +60°C
Storage	
Capacity loss per month at 20°C (% approx.)	3
Case Material	
Standard	ABS (UL94:HB)
Charge Voltage	
Float charge voltage at 20°C (V)/Block	13.65 (±1%)
Float charge voltage at 20°C (V)/Cell	2.275 (±1%)
Float Chg voltage tmp correction factor from std 20°C (mV)	-3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block	14.5 (±3%)
Cyclic (or Boost) charge Voltage at 20°C (V)/Cell	2.42 (±3%)
Cyclic Chg voltage tmp correction factor from std 20°C (mV)	-4
Charge Current	
Float charge current limit (A)	No limit
Cyclic (or Boost) charge current limit (A)	0.3
Maximum Discharge Current	
1 second (A)	36
1 minute (A)	12
Impedance	
Measured at 1 kHz (mΩ)	110
Design Life & Approvals	
EUROBAT Classification: Standard Commercial	3 to 5
Yuasa design life at 20°C (yrs)	up to 5
VdS (Germany)	VdS No: G 101094

Layout



3rd Party Cerfifications

ISO9001 - Quality Management Systems
UNDERWRITERS LABORATORIES Inc.

Cert. No.: FM 10626

Safety

Installation

Can be installed and operated in any orientation except permanently inverted.

Handles

Batteries must not be suspended by their handles (where fitted).

Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.

Data Sheet generated on 18/03/2016 – E&OE