

Dane aktualne na dzień: 10-05-2024 04:33

Link do produktu: <https://www.akumulatory24.pl/yuasa-np24-12i-p-3604.html>

YUASA NP24-12i 24Ah 12V AGM NP 24-12i



Cena brutto	430,00 zł
Cena netto	349,59 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Numer katalogowy	NP 24-12i
Kod EAN	4016138323702
Producent	Yuasa
Model	NP 24-12i
Napięcie [V]	12
Pojemność [Ah]	24
Polaryzacja	Prawy Plus
Długość [mm]	166
Szerokość [mm]	175
Wysokość [mm]	125
Waga [kg]	9,8

Opis produktu

Yuasa Technical Data Sheet

Yuasa NP24-12I Industrial VRLA Battery

Specifications

Nominal voltage (V)	12
10-hr rate Capacity to 1.8V/Cell at 20°C (Ah)	22.3
20-hr rate Capacity to 1.75V/Cell at 20°C (Ah)	24

Dimensions

Length (mm)	166 (±1)
Width (mm)	175 (±1)
Height (mm)	125 (±2)
Mass (kg)	9

Terminal Type

Threaded terminal - (M=Male or F=Female)	M5 (F)
Torque (Nm)	2.45

Operating Temperature Range

Storage (in fully charged condition)	-20°C to +60°C
Charge	-15°C to +50°C
Discharge	-20°C to +60°C

Storage

Capacity loss per month at 20°C (% approx.)	3
---	---

Case Material

Standard	ABS (UL94:HB)
FR version available	UL94:V0

Charge Voltage

Float charge voltage at 20°C (V)/Block	13.65 (±1%)
Float charge voltage at 20°C (V)/Cell	2.275 (±1%)
Float Chg voltage tmp correction factor from std 20°C (mV)	-3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block	14.5 (±3%)
Cyclic (or Boost) charge Voltage at 20°C (V)/Cell	2.42 (±3%)
Cyclic Chg voltage tmp correction factor from std 20°C (mV)	-4

Charge Current

Float charge current limit (A)	No limit
Cyclic (or Boost) charge current limit (A)	6

Maximum Discharge Current

1 second (A)	500
1 minute (A)	150

Short-Circuit Current & Internal Resistance

Internal resistance - according to EN IEC 60896-21 (mΩ)	22.19
Short-Circuit current - according to EN IEC 60896-21 (A)	656

Impedance

Measured at 1 kHz (mΩ)	11
------------------------	----

Design Life & Approvals

EUROBAT Classification: Standard Commercial	3 to 5 years
Yuasa design life at 20°C (yrs)	up to 5



Layout



3rd Party Certifications

ISO9001 - Quality Management Systems
ISO14001 - Environmental Management Systems
ISO45001 OHSAS Management Systems



Safety

Installation

Can be installed and operated in any orientation except permanently inverted.

Handles

Batteries must not be suspended by their handles (where fitted).

Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.



- Automaty sprzedające
- Aparatura kontrolno-pomiarowa
- Kasy fiskalne
- Komputery
- Narzędzia z napędem elektrycznym
- Parkometry
- Przenośne kamery video
- Systemy alarmowe
- Sprzęt medyczny
- Sprzęt morski i geofizyczny
- Systemy oświetlenia awaryjnego
- Systemy przeciwpożarowe
- Systemy zabezpieczeń
- Systemy zasilania energią słoneczną
- Telewizja kablowa
- Urządzenia biurowe
- Urządzenia automatyki przemysłowej
- Urządzenia gwarantowanego zasilania (UPS)
- Urządzenia telekomunikacyjne
- Zabawki