
Dane aktualne na dzień: 07-11-2026 12:01

Link do produktu: https://www.akumulatory24.pl/yuasa-rec10-12-10ah-12v-agm-rec-10-12-p-3081.html




YUASA REC10-12 10Ah 12V AGM REC 10-12

Cena brutto	**199,00 zł**
Cena netto	**161,79 zł**
Dostępność	**Dostępny**
Czas wysyłki	**24 godziny**
Kod producenta	**REC10-12**
Kod EAN	**5050694021336**
Producent	**Yuasa**
Napięcie [V]	**12**
Pojemność [Ah]	**10**
Długość [L mm]	**151**
Szerokość [W mm]	**65**
Wysokość [H mm]	**115**
Waga [kg]	**3,2**

Opis produktu


Yuasa Technical Data Sheet

Yuasa REC10-12 Industrial VRLA Battery



Specifications	
Nominal voltage (V)	12
10-hr rate Capacity to 1.8V/Cell at 20°C (Ah)	9.3
20-hr rate Capacity to 1.75V/Cell at 20°C (Ah)	10
Dimensions	
Length (mm)	151 (±1)
Width (mm)	65 (±1)
Height (mm)	112 (±2)
Height over terminals (mm)	115.5 (±2)
Mass (kg)	3.2
Terminal Type	
FASTON - Quickfit / release (JST where stated)	6.35
Operating Temperature Range	
Storage (in fully charged condition)	-15°C to +45°C
Charge	-15°C to +45°C
Discharge	-15°C to +45°C
Storage	
Capacity loss per month at 20°C (% approx.)	3
Case Material	
Standard	ABS (UL94:HB)
FR version available	UL94:V0
Charge Voltage	
Float charge voltage at 20°C (V)/Block	13.65 (±1%)
Float charge voltage at 20°C (V)/Cell	2.275 (±1%)
Float Chg voltage tmp correction factor from std 20°C (mV)	-3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block	14.52 (±3%)
Cyclic (or Boost) charge Voltage at 20°C (V)/Cell	2.42 (±3%)
Cyclic Chg voltage tmp correction factor from std 20°C (mV)	-4
Charge Current	
Float charge current limit (A)	2.5
Cyclic (or Boost) charge current limit (A)	2.5
Maximum Discharge Current	
1 second (A)	150
1 minute (A)	70
Cyclic Life Data	
100% DOD down to 80% capacity	300
75% DOD down to 80% capacity	500
50% DOD down to 80% capacity	600
25% DOD down to 80% capacity	1400
Impedance	
Measured at 1 kHz (mΩ)	12.1

Layout



3rd Party Certifications
ISO9001 - Quality Management Systems
UNDERWRITERS LABORATORIES Inc.

Cert. No.: FM 10626

Safety

Installation
Can be installed and operated in orientations up to 90° from the upright position.

Handles
Batteries must not be suspended by their handles (where fitted).

Vent valves
Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

Gas release
VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

Recycling
YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.

Data Sheet generated on 02/07/2025 – E&OE

Akumulatory przemysłowe YUASA serii REC są to 12 woltowe baterie. Ich pojemność zaczyna się od 10 Ah do 80 Ah. Są przeznaczone do pracy cyklicznej. Projektowana żywotność przy pracy cyklicznej wynosi 600 cykli.

Zalety akumulatorów:

- Akumulator VRLA o wysokiej wydajności cyklicznej
- Trwałe, ołowiane kraty wapniowe zapewniają doskonałą żywotność cykliczną
- Podwojony cykl życia w porównaniu ze standardową baterią VRLA
- Technologia maty szklanej absorpcyjnej (AGM)
- Rekombinacja gazu
- Doskonałe odzyskiwanie z głębokiego rozładowania
- Praca w dowolnej orientacji (z wyjątkiem skierowania biegunami w dół)

Zastosowanie:
-Automaty sprzedające
-Aparatura kontrolno-pomiarowa
-Kasy fiskalne
-Komputery
-Narzędzia z napędem elektrycznym
-Parkometry
-Przenośne kamery video
-Systemy alarmowe
-Sprzęt medyczny
-Sprzęt morski i geofizyczny
-Systemy oświetlenia awaryjnego
-Systemy przeciwpożarowe
-Systemy zabezpieczeń
-Systemy zasilania energią słoneczną
-Telewizja kablowa
-Urządzenia biurowe
-Urządzenia automatyki przemysłowej
-Urządzenia gwarantowanego zasilania (UPS)
-Urządzenia telekomunikacyjne
-Zabawki